Swelab<sup>™</sup> Alfa Plus hematology system. Equipped to deliver results you can trust.

A complete blood count is commonly requested to monitor patients' health status, and the results form the basis for decision-making regarding further testing, diagnosis, and treatment.

With its short analysis time, capillary sample inlet, and low maintenance needs, Swelab Alfa Plus hematology system contributes to efficient health assessments, from patient screening to monitoring of treatment efficacy:

- Complete blood count from a fingerstick sample.
- Rapid results to support early diagnosis and initiation of treatment.
- Robust equipment design that helps ensure instrument uptime.



Swelab Alfa Plus model characteristics	Basic	Standard	Cap	Sampler
Built-in tube mixer		٠		•
Micro-pipette adapter (MPA)		٠	•	•
Shear valve sample aspiration	•	٠	•	•
Pre-dilution mode	•	٠	•	•
Cap-piercing device			•	•
Autosampler				•

# **Technical specification**

## Parameters

16 for diagnostic use WBC, LYM, MID, GRAN, LYM%, MID%, GRAN%, RBC, MCV, HCT, PLT, MPV, HGB, MCH, MCHC, RDW% 6 for research use

RDW, PCT, PDW%, PDW, P-LCR, P-LCC

## Throughput

60 samples/hour 50 seconds, time to results, OT inlet

## Sample volume

Open tube (OT):	110 µL
Capillary (MPA):	20 µL
Prediluted:	20 µL
Cap piercer:	250 µL
Autoloader:	300 µL

#### Reagents

2 RFID locked reagents are used for analysis: Swelab AlfaDiluent Swelab AlfaLyse

## **Quality control**

Tri-level controls (L, N, H) QC statistics: Mean, SD, CV%, Levey-Jennings and X-bar

## Display

7 inch TFT touch screen

### Data storage capacity

50 000 samples

### Interface ports

4 USB ports, 1 LAN port that supports LIS/HIS communication through HL7 protocol

#### Printout

Postscript-compatible printers supporting PCL 3/5e

## Linearity ranges

PLT: 0-1800 × 10°/L RBC: 0.30-7.00 × 10<sup>12</sup>/L WBC: 0.20-130.0 × 10°/L HBC: 2.0-24.0 g/dL

## Dimension

295 mm (W) × 475 mm (D) × 395 mm (H) (Basic/Standard/Cap) 340 mm (W) × 475 mm (D) × 395 mm (H) (Sampler)

### Weight

≤ 18 kg (Basic/Standard/Cap)

≤ 22 kg (Sampler)

# boule.com

Swelab is a trademark of Boule Medical AB. © 2021–2022 Boule Diagnostics AB Boule Diagnostics AB, Domnarvsgatan 4, SE-163 53 Spånga, Sweden BPS38939-4 05/2023





