

Swelab™ Lumi hematology system. Enlightening your opportunities.

A complete blood count is often requested to assess a patient's general health status or to monitor disease progression and treatment.

Swelab Lumi hematology system provides access to a reliable, yet cost-effective hematology system, developed with the user in mind to facilitate operations. Built on robust software and hardware components, Swelab Lumi ensures a reliable performance, while keeping service and maintenance needs to a minimum. With its compact design, Swelab Lumi is well suited for the smaller laboratory:

- Developed to simplify work processes.
- Robust design ensures a reliable performance.
- Small footprint to suit the smaller laboratory.



Technical specification

Parameters

20 for diagnostic use:

RBC, MCV, HCT, RDW-CV, HGB, MCH, MCHC, PLT, MPV, WBC, LYM#, LYM%, MON#, MON%, NEU#, NEU%, EOS#, EOS%, BAS#, BAS%

9 for research use:

RDW-SD, PCT, PDW, P-LCC, P-LCR, AL#, AL%, IG#, IG%

Throughput

Up to 64 samples/h in CBC mode

Up to 48 samples/h CBC + 5-part WBC differential

Sample analysis

Samples: Venous blood, capillary blood, and pre-diluted

Sampling system: Open tube aspiration

Aspiration volume: CBC: 20 μ L and CBC + DIFF: 25 μ L

Reagents

3 RFID locked reagents and one cleaner used for analysis:

Swelab Lumi-D Diluent, Swelab Lumi-L1 Lyse, Swelab Lumi-L2 Lyse, and Boule EasyCleaner

Display

10.4 inch TFT touch screen

Quality control

Tri-level controls (L, N, H)

QC statistics: Mean, SD, CV%, Levey-Jennings and X-bar

Linearity ranges

PLT: 0–3000 $\times 10^9$ /L

RBC: 0–8.5 $\times 10^{12}$ /L

WBC: 0–300 $\times 10^9$ /L

HGB: 0–250 g/L

Data storage capacity

50 000 samples

Interface ports

4 USB ports, 1 LAN port that supports bidirectional LIS/HIS communication through HL7 protocol

Printout

External laser printer or inkjet printer, various printout formats and user-defined formats

Dimension

364 mm (W) \times 431 mm (D) \times 498 mm (H)

Weight

28 kg

boule.com

Swelab is a trademark of Boule Medical AB.

© 2021–2023 Boule Diagnostics AB

Boule Diagnostics AB, Domnarvsgatan 4, SE-163 53 Spånga, Sweden

BPS38940-5 11/2023

