



Swelab™ Lumi hematology system.

Enlightening your opportunities.

A complete blood count is often requested to assess a patient's general health status or to monitor disease progression and treatment.

Swelab Lumi hematology system provides access to a reliable, yet cost-effective hematology system, developed with the user in mind to facilitate operations. Built on robust software and hardware components, Swelab Lumi ensures a reliable performance, while keeping service and maintenance needs to a minimum. With its compact design, Swelab Lumi is well suited for the smaller laboratory:

- Developed to simplify work processes.
- Robust design ensures a reliable performance.
- Small footprint to suit the smaller laboratory.



Technical specification

Parameters

20 for diagnostic use:
RBC, MCV, HCT, RDW-CV, HGB, MCH, MCHC, PLT,
MPV, WBC, LYM#, LYM%, MON#, MON%, NEU#,
NEU%, EOS#, EOS%, BAS#, BAS%

11 for research use:
RDW-SD, PCT, PDW, P-LCC, P-LCR, AL#, AL%, IG#,
IG%, NRBC#, NRBC%

Throughput

Up to 64 samples/h in CBC mode
Up to 48 samples/h CBC + 5-part WBC differential

Sample analysis

Samples: Venous blood, capillary blood, and pre-diluted
Sampling system: Open tube aspiration
Aspiration volume: CBC: 20 μ L and CBC + DIFF: 25 μ L

Reagents

3 RFID locked reagents and one cleaner used for analysis:
Swelab Lumi-D Diluent, Swelab Lumi-L1 Lyse,
Swelab Lumi-L2 Lyse, and Boule EasyCleaner

Display

10.4 inch TFT touch screen

Quality control

Tri-level controls (L, N, H)
QC statistics: Mean, SD, CV%, Levey-Jennings and X-bar

Linearity ranges

PLT: 0–3000 $\times 10^9$ /L
RBC: 0–8.5 $\times 10^{12}$ /L
WBC: 0–300 $\times 10^9$ /L
HGB: 0–250 g/L

Data storage capacity

50 000 samples

Interface ports

4 USB ports, 1 LAN port that supports bidirectional LIS/HIS communication through HL7 protocol

Printout

External laser printer or inkjet printer, various printout formats and user-defined formats

Dimension

364 mm (W) \times 431 mm (D) \times 498 mm (H)

Weight

28 kg

boule.com

Swelab is a trademark of Boule Medical AB.
© 2021-2026 Boule Diagnostics AB
Boule Diagnostics AB, Fagerstagatan 7, 163 53 Spånga, Sweden
BPS38940-7 03/2026

